




MIDDLETON SOLAR
NSR1-E NET PYRRADIOMETER
APPLICATION NOTE

CE 2018



The Middleton Solar NSR1-E Net Pyrradiometer is for measuring both solar and thermal wavelengths as a single sum of energy; the net total radiation flux, downward and upward, through a horizontal plane. The NSR1-E has separate upper and lower thermoelectric sensors that are shielded by polythene dome windows. The domes are equally transparent to both shortwave radiation from the sun and long wave radiation emitted by the atmosphere or the Earth surface. The sensors have matched response times and balanced shortwave and longwave sensitivity.

Installation. Select a site that has an unobstructed view of the sky and the ground. Secure the output end of the handle and adjust so the instrument is horizontal, approximately 1-2m above the ground, with the bubble level facing upwards. The available *3-Axis Clamp* can facilitate mounting to a flat plate.


Connect the NSR1-E output lead to a data acquisition system; use differential inputs.

output lead cores	signal +ve signal -ve	yellow green
power supply cores	supply +ve (5 to 15VDC) supply 0V	red blue

Connect a power supply to the instrument; keep the supply 0V separate from the -ve signal connection. The output signal is an analogue voltage representing the difference of total downward hemispherical irradiance and total upward hemispherical irradiance. The typical fullscale output is -0.2 to +1.5 V.

Water on the domes (rain or dew) is a strong absorber of near IR radiation and can cause temporary measurement errors to the thermal component of the radiation.

Maintenance. Keep the polythene domes clean and free from debris; use water and mild detergent only. Replace the domes every six months. Bi-annual calibration is recommended, at which time the desiccant should be replaced.



Technical Specification

sensitivity	1 mV/W.m ⁻²
calibration traceability	LW: WISG (World Infrared Standard Group) SW: WRR (World Radiometric Reference)
resolution	< 2 W.m ⁻²
spectral range	0.3 to 60 µm
spectral selectivity	< 5%
field of view	2 x 180°
response time (95%)	11s (typical)
irradiance	-250 to +2,000 W.m ⁻²
impedance	80 Ω
power requirement	5 – 15 VDC; < 6mA
operating temperature	-35 to +60°C
non-linearity	< 3%
temperature dependence of sensitivity	< 3% (-20 to +50°C)
temperature gradient offset (5°C /hr)	< 4 W.m ⁻²
directional response (w.r.t 1,000 W.m ⁻²)	SW: < 25 W.m ⁻² (0-80°) LW: not relevant to isotropic IR
uncertainty in daily total (95% level)	< 5%
level accuracy	0.4°
desiccant	orange silica gel (non-toxic)
sensors	thermopile, flat white receiver with black centre
windows	polythene dome, Ø29x0.4mm
output lead	6m, with in-line connector at handle
construction	anodized aluminium; stainless steel
IP rating	sealed to IP67
dimensions & weight	head 66x40x130mm; handle Ø16x690; 0.7kg
shipping size & weight	Ø90 x 850mm; 1kg

Spare Parts & Available Options

Polythene Dome (pair), P/No 123.1066

Dome O-ring (pair), P/N 123.0080

Additional output lead length, up to 20m

3-Axis Clamp (for mounting to a flat plate), P/N 123.9100 (pictured)

